



## TECHNICAL SPECIFICATION

	TYPE	FLEXI	SONIC	8K	PRODUCTION
TRANSMISSION	Resolution	HD/2K/UHD/4K	HD/2K/UHD/4K	UHD/4K/8K	HD/2K/UHD/4K
	Frame rates	≤ 60	≤ 60	≤ 60	≤ 60
	Channels (2K,4K,8K)	8/2/0	4/1/0	0/4/1	4/1/0
	Video sampling	YCbCr 4:2:2 10bit	YCbCr 4:2:2 10bit	YCbCr 4:2:2 10bit	RGB up to 4:4:4 12bit
	Compression	JPEG2000/uncompressed	JPEG2000	JPEG2000	JPEG2000/uncompressed
	Recovery	FEC 20x5/10x10/custom			
INTERFACES	Video	8x 1,3,6,12G-SDI programmable in/out			
	Monitor out	SDI/HDMI			
	Audio	embedded, 16 channels			
	IP Network	2xSFP+, 2xSFP (2+0,1+1)			
	Management	touch panel / RJ45			
OTHER	Power	AC 90-260V (43-63Hz) 120W or DC 36-76V 120W			
	Dimensions[mm]	1RU - H44xW444xD221			
OPTIONS	Dual PS	AC/AC, AC/DC, DC/DC			
	Portable version	H44xW221xD221 with external PS			