

**TECHNICAL SPECIFICATION**

TYPE		FLEXI
TRANSMISSION	Resolution	HD/2K/UHD/4K
	Frame rates	up to 60
	Channels (2K,4K)	8/2
	Video sampling	YCbCr 4:2:2 10bit
	Compression	JPEG2000
	Recovery	FEC 20x5/10x10/custom
INTERFACES	Video	8x 1,3,6,12G-SDI programmable in/out
	Monitor out	SDI/HDMI
	Audio	embedded, 16 channels
	IP Network	2xSFP+, 2xSFP (2+0,1+1)
	Management	touch panel / RJ45
OTHER	Power	AC 90-260V (43-63Hz) 120W or DC 36-76V 120W
	Dimensions[mm]	1RU - H44xW444xD221
OPTION	Dual PS	AC/AC, AC/DC, DC/DC
	Portable version	H44xW221xD221 with external PS

Redcap solutions s.r.o., Na viničních horách 1831/13, 16000 Prague 6, Czech republic - sales@redcap-int.com



TECHNICAL SPECIFICATION

TYPE		MW LINKS
TRANSMISSION	54	HD/2K/UHD/4K
	Frame rates	up to 60
	Channels (2K,4K)	8/2
	Video sampling	YCbCr 4:2:2 10bit
	Compression	JPEG2000
	Recovery	FEC 20x5/10x10/custom
INTERFACES	Video	8x 1,3,6,12G-SDI programmable in/out
	Monitor out	SDI/HDMI
	Audio	embedded, 16 channels
	IP Network	6x RJ45 (4x PoE++)
	Management	touch panel / RJ45
OTHER	Power	AC 90-260V (43-63Hz) up to 500W (depending on number of PoE++ ports used)
	Dimensions[mm]	case 2U H100xW500xD420
OPTION	Dual PS	N/A
	Portable version	N/A

Redcap solutions s.r.o., Na viničních horách 1831/13, 16000 Prague 6, Czech republic - sales@redcap-int.com